

# UV Intensity Meters

The measurement of the UV irradiance is the most effective way to monitor the useful life of any UV light source. UVP meters ensure maximum operating efficiency of any UV system.

## UVX Digital Radiometers

The **UVX Radiometer** is used with one of the three sensors (ordered separately) for measuring shortwave (254nm), longwave (365nm) and midrange (302nm) UV wavelengths.

- Choose from three sensors: UVX-25 shortwave, UVX-31 midrange or UVX-36 longwave
- The UVX range switch provides selection from three intensity ranges:
  - 0 to 20 mW/cm<sup>2</sup>
  - 0 to 2000 μW/cm<sup>2</sup>
  - 0 to 200 μW/cm<sup>2</sup>
- The attenuator extends the reading range up to 200mW/cm<sup>2</sup>
- 9-volt battery for up to 120 hours
- A port enables connection to a chart recorder for continuous monitoring

Recalibration of meters and sensors is recommended every six months.

Sensor Cable Length: 3 feet (0.9 m)  
 Weight: 9.4 oz (0.3 kg)  
 Display: 3.5 digit LCD  
 Operating Environment: Temperature: 0 to 50°C  
 Humidity: 5% to 90% Relative Humidity

**UVX Dimensions:** 6.2L x 2H x 3.6W in. (157 x 51 x 91 mm)

## J-Series Analog UV Meters

**J-Series meters** are photovoltaic devices for accurate and repeatable readings of shortwave and longwave UV sources. The durable plastic housing withstands heavy, sustained use.

**J-221 Meter** measures the intensity of 365nm longwave UV. The sensor is sensitive within a range of 300-400nm with a peak sensitivity at 365nm. Intensity readings are 0-1200 μW/cm<sup>2</sup> (A Scale) and 1000-6000 μW/cm<sup>2</sup> (B Scale). J-221 Meter complies with MIL STD 45662-A.

**J-225 Meter** measures the intensity of 254nm shortwave UV. The sensor is sensitive within a range of 220-280nm with peak sensitivity at 254nm. Intensity readings at 0-2400 μW/cm<sup>2</sup> (A scale) and 2000-12000 μW/cm<sup>2</sup> (B Scale).

- Self-powered for maximum portability
- Two scales for low and high intensity readings
- A three foot (0.9m) cord connects the sensor to the meter for remote readings
- Infrared filter assures accurate readings when measuring light sources producing infrared radiation
- The 5X attenuation screen can be used for very high intensity lamp measurements
- All meters and sensors are calibrated to meet UVP's published standards and NIST



*UVX Radiometer Select from three UV sensors for measuring UV intensity.*

### Ordering Information

<b>UVX Radiometer</b>	97-0015-02
<b>Attenuator, 10:1</b>	98-0035-01
<b>9V Battery</b>	45-0012-01
<b>UVX-25 Sensor</b> Calibration Point: 254nm Bandpass: 250-290nm	97-0016-01
<b>UVX-31 Sensor</b> Calibration Point: 310nm Bandpass: 280-340nm	97-0016-04
<b>UVX-36 Sensor</b> Calibration Point: 365nm Bandpass: 335-380nm	97-0016-02



*J-221 and J-225 Meters measure UV sources*

### Ordering Information

<b>J-221 Longwave Meter 365nm UV</b>	97-0003-01
<b>J-225 Shortwave Meter 254nm UV</b>	97-0004-01

### Dimensions:

3H x 3D x 3W in. (76 x 76 x 76 mm)  
 Weight: 9 oz (0.25 kg)