

恒溫水槽

規格說明

溫度範圍：室溫加5°C~100°C

溫度控制器：微電腦 P.I.D.自動演算功能、雙顯示

溫度控制精度：±0.1°C

測溫體：PT100Ω白金測溫棒

加熱器：不銹鋼管製成加熱棒

材質：內不銹鋼板 SUS304、外鍍鋅鋼板粉體烤漆

攪拌幫浦：不銹鋼幫浦、攪拌循環水槽，使槽內水溫分佈均勻



G-10 / G-20



薄膜觸控



圈孔蓋



G-30 / G-50



屋形蓋

型 式	G-10	G-20	G-30	G-50
內部尺寸	W295xD235xH150mm	W495xD295xH150mm	W500xD300xH200mm	W650xD350xH300mm
外部尺寸	W325xD280xH200mm	W540xD325xH200mm	W680xD335xH250mm	W855xD480xH360mm
內 容 量	10L	20L	30L	60L
加 熱 器	800W	1200W	2000W	3500W
操作空間	W200x235mm	W400x295mm	W500x300mm	W650x350mm
電 源	110V/220V 7.2A/3.5A	110V/220V 11A/5.5A	110V/220V 18A/9A	220V 16A

註明：外部循環裝置及屋形蓋、圈孔蓋、夾具請另購，接受更大尺寸容量訂做。
可選擇全面薄膜觸控面板同樣具有 P.I.D 功能。